

VECTAMAXX RSL™ COMMERCIAL REVERSE OSMOSIS SYSTEMS

HP – High Pressure

MODEL	RSL2400 RSL2400HP	RSL4800 RSL4800HP	RSL7200 RSL7200HP	RSL9600 RSL9600HP
MEMBRANE SIZE	4 X 40	4 X 40	4 X 40	4 X 40
# OF MEMBRANES	1	2	3	4
NOMINAL PRODUCTION (GPD)	2400	4800	7200	9600
OPERATING PRESSURE (PSI)	130	130	140	130
HP	230	230	230	230
RECOVERY RATE	60% @ <1000 TDS, 40% @ >1000 TDS			
HP	60% @ <2000 TDS, 40% @ >4000 TDS			
OPERATING VOLTAGE	230 v	230 v	230 v	230 v
SOURCE WATER	Tap or brackish	Tap or brackish	Tap or brackish	Tap or brackish
INLET (INCH)	1 FNPT	1 FNPT	1 FNPT	1 FNPT
PERMEATE (INCH)	1/2 QC	1/2 QC	1/2 QC	1/2 QC
UNIT DIM. (DxWxH)	24"x31"x50"	24"x31"x50"	24"x31"x50"	24"x31"x50"
WEIGHT	96/124	114/142	132/160	154/178